

SRS Getriebefluid SBL 75W-90



High-Performance Low-Friction Multi-Purpose Gear Oil

March 2023

Characteristics

SRS Getriebefluid SBL 75W-90 is a high performance multi-purpose gear oil especially for heavily loaded axle drives and manual transmissions. The viscosity adjustment SAE 75W-90 guarantees both good low temperatures fluidity and a strong lubricating film at high temperatures even at longest drain intervals. A high fuel saving is achieved by the special low friction properties of SRS Getriebefluid SBL 75W-90.

Application

SRS Getriebefluid SBL 75W-90 is for universal application in gearboxes, auxiliary drives and rear axles, including heavily loaded hypoid meshed drive axles and can be used in commercial vehicles, agricultural machines, construction machines or passenger cars. The requirements of API GL-4 and GL-5 are met with great reserve; longer oil change intervals reduce maintenance costs and the economy increases.

Specifications

- SAE Grade 75W-90
- API GL-4 / GL-5
- API MT-1
- SAE J 2360 (MIL-PRF-2105 D/E)

Recommendations

- MAN 341 Typ Z2
- MAN 341 Typ GA1
- MAN 342 Typ M3
- Scania STO 1:0
- Scania STO 1:1 G
- ZF TE-ML 02B, 05A, 07A, 12L, 12N, 16B, 17B, 19B, 21A
- Volvo Transmission Oil 97 312
- Robert Bosch TE-ML 08
- Mack GO-J
- ArvinMeritor O-94
- Iveco
- DAF

SRS Getriebefluid SBL 75W-90 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Getriebefluid SBL 75W-90
SAE Grade	SAE J 306	75W-90
Density at 15°C	DIN 51 757	0.878
Dyn. Viscosity at -40°C	DIN 51 398	130,000
Kin. Viscosity at 40°C	DIN EN ISO 3104	116
Kin. Viscosity at 100°C	DIN EN ISO 3104	16.5
Viscosity Index (VI)	DIN ISO 2909	154
Flash Ppoint COC	DIN ISO 2592	202
Pour Point	DIN ISO 3016	-45

The above values may vary within the commercial limits.

Made in Germany