

# SRS Rekord 15/40

## Multigrade Engine Oil



November 2022

### Characteristics

**SRS Rekord 15/40** is a multigrade engine oil for use in diesel and gasoline engines. The all season 15W-40 viscosity grade provides easy starting in winter high temperature stability even at extreme stress. Shear stable viscosity index improvers are responsible for the stay-in-grade characteristic throughout the entire oil drain interval. High quality base oils together with selected additives will assure excellent antiwear protection and engine cleanliness. The formation of black sludge will be avoided.

### Application

**SRS Rekord 15/40** was developed as universal engine oil for mixed vehicle fleets and construction industry. The performance meets the requirements of all commercial and passenger car diesel engines as well as of all gasoline engines with or without turbochargers. SRS Rekord 15/40 corresponds to the earlier ACEA A2/B2 and E2.

### Specifications

- SAE Grade 15W-40
- API SJ/CF-4

### Recommendations

- MAN 271
- Volvo VDS
- MTU MTL 5044 Type 1
- MB 228.1
- MB 229.1
- Allison C-4

SRS Rekord 15/40 is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS Rekord 15/40
SAE Grade	SAE J 300	15W-40
Density at 15°C	DIN 51 757	0.882
Dyn. Viscosity at -20°C	ASTM D 5293	6,520
Kin. Viscosity at 40°C	DIN EN ISO 3104	105
Kin. Viscosity at 100°C	DIN EN ISO 3104	14.1
Viscosity Index (VI)	DIN ISO 2909	136
Flash Point COC	DIN ISO 2592	250
Pour Point	DIN ISO 3016	-24
Total Base Number	DIN ISO 3771	7.7

The above values may vary within the commercial limits.

**Made in Germany**

